



Great features,
simple to use.

D-545 Zoom


[Overview](#)
[Features and Benefits](#)
[Specs](#)
[Package Contents](#)
[Accessories](#)
[Software](#)
[Brochures and Manuals](#)
[Compare](#)
[Free Photo Lessons](#)

D-545 Zoom

Designed to Do More.

One touch is all it takes to go from beginner to expert with the D-545. Spin the convenient mode dial to switch between 19 automatic scene modes. Press the separate buttons to quickly shoot, play back, or delete pictures. Push the menu pad to display the in-camera Help Guide for quick photo tips. And see the results in clear, vibrant fashion thanks to a 4.0 megapixel CCD, 12x total zoom, and so much more.

Specs

Estimated Retail Price:

\$199.99

Prices may vary, as each Olympus dealer determines what price to charge.

Free Photo Lessons

Improve your photography skills by taking lessons online.



CCD Imager	4.0 megapixel effective, 4.0 megapixel gross, 1/2.5" CCD
Lens	6.3 – 18.9mm (38 – 114mm equivalent in 35mm photography), 6 lenses in 5 groups (including 3 aspherical elements)
Seamless Digital Zoom	Seamless to 12x (3x optical and 4x digital combined)
Aperture Range	f2.8 – f4.9 (adjustable in 1/3 EV step)
Shutter Speeds	1/2000 sec – 4 sec
ISO	Auto (50 – 250) (equivalent)
Recording Mode(s)	Still Image: DCF Standard (JPEG, EXIF 2.21), PIM II Movie Mode: DCF Standard (QuickTime® motion JPEG)
Adjustable Resolutions	2288 x 1712, SHQ/HQ 1600 x 1200, SQ1 Normal 640 x 480, SQ2 Normal
DPOF (Digital Print Order Format)	PictBridge and DPOF
Optimum Image Enlargement	
Image Adjustment Modes	Still Image: Index display, Up to 5x enlargement, Slide show, Scene rotation
Image Effects	Still Image: Black & White, Sepia, Resize, Rotation, Frame integration Movie: Normal edit, Frame index
Panorama	Up to 10 frames automatically stitchable with Olympus Master Software when using Olympus brand xD-Picture Card™
Sequence	1.3 frames per second up to 7 frames
Viewfinder	N/A
LCD	1.8" Color TFT, approx. 85,000 pixels

Focusing System	TTL Contrast detection
Focusing Ranges	Normal mode: 19.7" (0.5m – infinity) Macro mode: 7.9" – 19.7" (0.2m – 0.5m) Super Macro Mode: 0.8" (20mm)
Exposure Control	±2 EV steps in 1/3 EV steps
Metering System	Digital ESP, Spot
White Balance System	iESP2 multi-pattern auto TTL
Flash	Built-in
Flash Modes	Auto (for low light and backlit conditions) Red-eye Reduction Fill-in Off
Flash Working Range	Wide: 12.5 ft. (3.8m); Tele 7.2 ft. (2.2m)
Flash Charging Time	
Removable Media Card	xD-Picture Card™ (16, 32, 64, 128, 256, 512MB and 1GB)
Selftimer/Remote	12 seconds/Auto
Setting Memorization	On/Off (Hold changes/Reset to default settings)
Outer Connectors	USB connector (Auto-Connect) and DC input
Auto-connect USB	2.0 Full Speed
Image Playback	Still Image: Index display, Up to 5x enlargement, Slide show, Scene rotation Movie: Normal, Reverse, Frame-by-frame
Operating Environment	Operation: 32° – 104°F (0° – 40°C), 30% – 90% humidity Storage: -4° – 140°F (-20° – 60°C), 10% – 90% humidity
Power Supply	AA Batteries (x2), Lithium (CR-V3), AC Adapter
Date/Time Calendar	Simultaneous recording into image data, Automatic up to 2099
Calendar	Automatic up to 2099
Size	4.2"W x 2.2"H x 1.4"D (106.0mm x 56.0mm x 36.2mm)
Weight	4.9 oz. (140g) without battery and media card
Number of Storable Photos	

	Quality Mode	Resolution	128MB xD-Picture Card	512MB xD-Picture Card
Still image Unit: shots	SHQ	2288 x 1712	44 shots	178 shots
	HQ	2288 x 1712	130 shots	523 shots
	SQ1	1600 x 1200	257 shots	1030 shots
	SQ2	640 x 480	1330 shots	5324 shots
Movie Unit: min.	HQ	320 x 240	193 sec.	774 sec.
	SQ	320 x 240	387 sec.	1548 sec.

All capacity figures are approximate.



[Digital Cameras](#) | [Film Cameras](#) | [Voice Recorders](#) | [Binoculars](#) | [Photo Printers](#) | [Accessories](#) | [Archived Products](#)

© 2005 Olympus America Inc.

[Privacy Statement](#)

[Terms of Use](#)

[Sitemap](#)

© 2005 Olympus Imaging America Inc.